

5. Fire Fighting Measures

Hazards from combustion products:	Non-combustible liquid
Fire and Explosion Hazards: Precautions for fire fighters and special protective equipment:	Can form flammable mixtures with air and flash at room temperature. Fire fighters must wear suitable protective clothing. Avoid spreading burning liquid with water used for cooling purposes.
Suitable Extinguishing Media:	Use the appropriate extinguishing media for the surrounding fire. Use CO ₂ (Carbon Dioxide), dry chemical, water or foam.

6. Accidental Release Measures

Methods and materials for containment and clean up:	Eliminate any ignition source. Dike or impound spilled material. Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect into vapour tight containers and dispose of properly.
---	--

7. Handling and Storage

Conditions for safe storage:	Store product in a cool, dry environment away from sources of ignition.
Precautions for safe handling:	Keep container closed when not in use. Use only with adequate ventilation.
Work/Hygienic practices:	Wash hands thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Occupational Safety Limits:	SEVERELY HYDROTREATED PETROLEUM DISTILLATE = 5mg/m ³ as mist
Engineering Controls:	Use with adequate ventilation to keep product vapour concentrations below specified TLV
Eye/Face Protection:	Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury.
Skin Protection:	Wear gloves and appropriate protective clothing as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.
Respiratory Protection:	General room ventilation is normally adequate. Avoid breathing the product mist. The use of an OSH approved respirator is recommended whenever the airborne concentrations exceed the TLV.

